



**acniti LLC**  
1-2-9 Nyoidani  
Minoh Osaka  
562-0011  
Japan

**acniti**

## hydrogen galf

The custom design ultrafineGaLF drinking water, fills the need, for a unit for the food and beverage industry to produce ultrafine bubbles or nanobubbles. The ultrafineGaLF custom design unit has the ability to be Clean in Place. CIP is a method of cleaning the interior surfaces of pipes, vessels, process equipment, filters and associated fittings, without disassembly. The GaLF custom is suitable for use with Ozone, Hydrogen, Oxygen and Nitrogen.

# hydrogen galf

## custom design ultrafinegalf hydrogen nanobubble drinking water

- ✓ Unit installed in various drinking water bottling companies
- ✓ Ability to produce hydrogen ultrafine bubble drinking water
- ✓ Ability to produce oxygen ultrafine bubble drinking water
- ✓ The version with Clean-In-Place fittings and pipe
- ✓ Nanobubbles easily generated
- ✓ Nanobubble diameter 80 to 200 nm
- ✓ Automatic gas intake no need to pressurize the gas
- ✓ Suitable for use with Ozone, Hydrogen, Oxygen and Nitrogen
- ✓ Nanobubble generator made from sanitary pipe and fittings

The custom design drinking water unit, is introduced for the high demand to produce nanobubble water with hydrogen bubbles or high oxygen content water for the food and beverage industry. The custom units are installed at various drinking water bottling companies in Japan. The largest unit at the moment has a production capacity of 4,000 liters per hour, around 1,000 gallons. One of the main advantages of this unit is that it has the option to be Cleaned-In-Place, which is a requirement in many countries for certification.

The custom design drink water unit, is build according to the specifications of the customer, to make integration with other equipment easy.

Contact us for your project, to have nanobubbles implemented in the food and beverage industry.

# ultrafine galf drinkwater unit specs

Description			Metric	Imperial
1 Model name			ultrafine GaLF drinkwater unit	ultrafine GaLF drinkwater unit
2 Model number			GaLF-CIP	GaLF-CIP
Liquid			Metric	Imperial
3 Strainer availability and size				
Ambient			Metric	Imperial
4 Ambient temperature maximum			35 °C	95 °F
5 Relative humidity minimum			45 %	45 %
6 Relative humidity maximum			85 %	85 %
Gas			Metric	Imperial
7 Gas quality				
8 Gas remark			Air, O2, Ozone O3, H2, CO2, N2	Air, O2, Ozone O3, H2, CO2, N2
Connections			Metric	Imperial
9 Water inlet				
10 Water outlet				
11 Gas inlet				
Remarks				
12 Other remarks			<input checked="" type="checkbox"/> Recommended: 2.2 ppm which will lead to a slowing to 1.6ppm in a short time	